

U S E A N D C A R E S T A I N L E S S S T E E L



All cleaning and polishing of Stainless Steel finishes should be done with a soft, 100% lint-free or micro-fiber cloth. Fingerprints are the most common item to be cleaned from stainless surfaces. These can be easily removed with any household brand window and glass cleaner (not an abrasive). Heavier dirt or stains can be removed with a nonabrasive stainless steel cleaner or polish. If using a cleaner or polish, be sure to test a small, inconspicuous area first and always wipe with the grain direction on the stainless steel.

U S E A N D C A R E P O W D E R C O A T



All cleaning of Powdercoat finishes should be done with a soft, 100% lint-free or micro-fiber cloth. Powdercoat finishes can be treated like most other paints and benefit from regular cleaning. The frequency of cleaning depends on the environment. For areas in normal urban environments, we recommend cleaning once every 6 months. A mild detergent or ideally a car shampoo applied with a soft cloth should be used (not an abrasive). Any dirt adhering to the powdercoat should be removed first. If this is not sufficient to remove stubborn soiling, the following products have been tested for use:

- Ajax Cream
- Liquid Gumption
- Flash (in water)
- Ajax Liquid (in water)

Never use solvents such as acetone, contact cleaners, thinners or Methyl Ethyl Ketone (MEK) to clean powdercoat finishes. These solvents are very damaging to the powdercoat finish and will remove the finish altogether.

USE AND CARE OUTDOOR WOOD PRODUCTS



CLEAN-UP AND MAINTENANCE: Clean spills right away with a damp cloth. To maintain the products protective characteristics, apply a maintenance coat when visibly required. Test wood for absorbency by sprinkling water on the surface – if water is absorbed within 30 seconds – 2 minutes, depending on climate, the surface is ready for finishing. Clean and prepare surface as specified under **GENERAL SURFACE PREPARATION**. Areas that show minimal wear should only be lightly coated. Lighter colors may require more frequent maintenance.

GENERAL SURFACE PREPARATION: All wood surfaces must be thoroughly clean, dry and free of dirt, grease, grime, mildew, mill glaze, and previous coatings before application. Spray all wood surfaces with clean water, completely wetting the wood. Apply a cleaning solution of four (4) ounces of 100% powdered Tri-Sodium Phosphate (TSP) or phosphate-free substitute with one (1) quart of liquid bleach and three (3) quarts of water to the wood surfaces with a garden sprayer or a heavy nap roller cover. Let the solution dwell on the surface for 15-20 minutes. Scrub surface with a hard bristle brush for 15-20 minutes to help remove mill glaze or weathering.

Do not allow solution to dry on the wood surface. Power-wash the wood surface with clean fresh water using 500-800 psi with the nozzle 8-12 inches away to remove cleaning solution. Allow the surface to dry for 48 hours, or to have a moisture content of 18% or less before application. Sand all cleaned wood using 80-120 grit sandpaper for vertical surfaces and 60-80 grit sandpaper for horizontal surfaces. ***Always sand in direction of the wood grain and remove sanding dust. Finish should be applied within one week of preparation, provided that the surface remains free of dirt, grease, grime, and mildew.***

cont'd on next page

USE AND CARE WOOD MAINTENANCE



cont'd from previous page

PRECAUTIONS: Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **DANGER – RAGS, STEEL WOOL OR WASTE SOAKED WITH CETOL SRD SEMI-TRANSPARENT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL, OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.**

FIRST AID: If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call a **POISON CENTER** or doctor/physician. Keep out of the reach of children.

EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.)